

# EYEWASH

## MODEL: 2221S

Model 2221S, pedestal-mounted eyewash unit with a stainless-steel bowl, stainless steel eyewash spray heads, an inline strainer, and a stainless-steel stay-open 1/2" ball valve with a push handle.

ANSI Z358.1 2014 complied design delivers consistent water spray for effective decontamination.



### Features

- Pedestal-mounted eyewash unit with a stainless-steel bowl, stainless steel eyewash spray heads, an inline strainer, and a stainless-steel stay-open 1/2" ball valve with a push handle.
- Valve: 1/2" NPT stainless steel stay-open ball valve with a stainless-steel push handle and an inline strainer.
- Spray Head Assembly: SS316 eyewash heads with integral flip dust covers, internal flow controls (0.4 GPM), and filters to remove debris from the water.
- Water Supply: 1/2" NPT female threaded stainless steel side or top inlet.
- Drain water: 1-1/4" NPT female outlet.
- Piping & Mounting: Schedule 40 stainless steel piping and a stainless-steel floor flange.
- Universal Sign: ANSI compliant, vertical identification sign (eyewash sign)
- Eyewash: Eyewash with stainless steel 316 bowl, stainless steel nozzles, fitted with 0.4 GPM flow regulators.
- Stainless steel foot pedal actuator

### Optional Features

- Scald protection valve (SPV)
- Freeze protection valve
- In-line strainer
- Drench hose

Model 2111SP, pedestal-mounted eyewash unit with a stainless-steel bowl, stainless steel eyewash spray heads, an inline strainer, and a stainless-steel stay-open 1/2" ball valve with a push handle.

ANSI Z358.1 2014 complied design delivers consistent water spray for effective decontamination.



### Features

- Pedestal-mounted eyewash unit with a stainless-steel bowl, stainless steel eyewash spray heads, an inline strainer, and a stainless-steel stay-open 1/2" ball valve with a push handle.
- Valve: 1/2" NPT stainless steel stay-open ball valve with a stainless-steel push handle and an inline strainer.
- Spray Head Assembly: SS316 eyewash heads with integral flip dust covers, internal flow controls (0.4 GPM), and filters to remove debris from the water.
- Water Supply: 1/2" NPT female threaded stainless steel side or top inlet.
- Drain water: 1-1/4" NPT female outlet.
- Piping & Mounting: Schedule 40 GI piping and a floor flange.
- Universal Sign: ANSI compliant, vertical identification sign (eyewash sign)
- High durability stainless steel foot pedal for activation
- Eyewash: Eyewash with stainless steel 316 bowl, stainless steel nozzles, fitted with 0.4 GPM flow regulators.

### Optional Features

- Scald protection valve (SPV)
- Freeze protection valve
- In-line strainer
- Drench hose

Model 2111P, pedestal-mounted eyewash unit with a ABS plastic bowl, stainless steel eyewash spray heads, an inline strainer, and a stainless-steel stay-open 1/2" ball valve with a push handle.

ANSI Z358.1 2014 complied design delivers consistent water spray for effective decontamination.



### Features

- Pedestal-mounted eyewash unit with ABS bowl, stainless steel eyewash spray heads, an inline strainer, and a stainless-steel stay-open 1/2" ball valve with a push handle.
- Valve: 1/2" NPT stainless steel stay-open ball valve with a stainless-steel push handle and an inline strainer.
- Spray Head Assembly: SS316 eyewash heads with integral flip dust covers, internal flow controls (0.4 GPM), and filters to remove debris from the water.
- Water Supply: 1/2" NPT female threaded stainless steel side or top inlet.
- Drain water: 1-1/4" NPT female outlet.
- Piping & Mounting: Schedule 40 GI piping and a stainless-steel floor flange.
- Universal Sign: ANSI compliant, vertical identification sign (eyewash sign)
- Eyewash: Eyewash with ABS bowl, stainless steel nozzles, fitted with 0.4 GPM flow regulators.

### Optional Features

- Scald protection valve (SPV)
- Freeze protection valve
- Stainless steel foot pedal actuator
- In-line strainer
- Drench hose



[www.smithapplied.com](http://www.smithapplied.com)



7040 Virginia Manor Rd.  
Beltsville, MD 20705 USA  
Phone: +1 (301) 842-4236  
Email: [info@smithapplied.com](mailto:info@smithapplied.com)