

4221SF is a shower and eyewash combination with heavy duty SS 316 piping, SS 316 shower head and eyewash bowls, with a pull rod mechanism for shower and foot pedal for eyewash.

ANSI Z358.1 2014 complied design delivers consistent water spray for effective decontamination. Pedestal-mounted emergency shower with a stainless-steel showerhead and a stainless-steel stay-open ball valve.

Features

- Pedestal-mounted emergency shower with a stainless-steel showerhead and a stainless-steel stay-open ball valve with a pull rod
- **Showerhead:** Stainless steel showerhead with 20 gallons per minute flow regulator.
- **Valve:** Hands free stainless-steel stay-open ball valve. Unit is provided with a stainless-steel actuator arm and a stainless-steel pull rod.
- **Water Supply:** 1-1/4" NPT female threaded stainless steel side or top inlet.
- **Piping & Mounting:** Schedule 40 stainless steel piping and a stainless-steel floor flange.
- **Universal Sign:** ANSI compliant, vertical identification sign (shower/eyewash sign)
- **Eyewash:** Eyewash with stainless steel 316 bowl, stainless steel nozzles, fitted with 0.4 GPM flow regulators.
- High durability stainless steel foot pedal for activation
- Scald protection valve (SPV)

Optional Features

- Freeze protection valve
- In-line strainer
- Drench hose



4211SG is a shower and eyewash combination with heavy duty GI piping, SS 316 shower head and eyewash bowls, with a pull rod mechanism for shower and stainless-steel push handle for eyewash.

ANSI Z358.1 2014 complied design delivers consistent water spray for effective decontamination. Pedestal-mounted emergency shower with a stainless-steel showerhead and a stainless-steel stay-open ball valve.



Features

- Pedestal-mounted emergency shower with a stainless-steel showerhead and a stainless-steel stay-open ball valve with a pull rod
- **Showerhead:** Stainless steel showerhead with 20 gallons per minute flow regulator.
- **Valve:** Hands free stainless-steel stay-open ball valve. Unit is provided with a stainless-steel actuator arm and a stainless-steel pull rod.
- **Water Supply:** 1-1/4" NPT female threaded stainless steel side or top inlet.
- **Piping & Mounting:** Schedule 40 GI piping and a floor flange.
- **Universal Sign:** ANSI compliant, vertical identification sign (shower/eyewash sign)
- **Eyewash:** Eyewash with stainless steel 316 bowl, stainless steel nozzles, fitted with 0.4 GPM flow regulators.

Optional Features

- Freeze protection valve
- Scald protection valve (SPV)
- Stainless steel foot pedal actuator
- In-line strainer
- Drench hose

4211PF is a shower and eyewash combination with heavy duty GI piping, ABS plastic shower head and eyewash bowls, with a pull rod mechanism for shower and stainless-steel push handle for eyewash.

ANSI Z358.1 2014 complied design delivers consistent water spray for effective decontamination. Pedestal-mounted emergency shower with a ABS plastic showerhead and a stainless-steel stay-open ball valve.

Features

- Pedestal-mounted emergency shower with a stainless-steel showerhead and a stainless-steel stay-open ball valve with a pull rod
- **Showerhead:** ABS plastic showerhead with 20 gallons per minute flow regulator.
- **Valve:** Hands free stainless-steel stay-open ball valve. Unit is provided with a stainless-steel actuator arm and a stainless-steel pull rod.
- **Water Supply:** 1-1/4" NPT female threaded stainless steel side or top inlet.
- **Piping & Mounting:** Schedule 40 stainless steel piping and a floor flange.
- **Universal Sign:** ANSI compliant, vertical identification sign (shower/eyewash sign)
- **Eyewash:** Eyewash with ABS plastic bowl, stainless steel nozzles, fitted with 0.4 GPM flow regulators.



Optional Features

- Scald protection valve (SPV)
- Freeze protection valve
- Stainless steel foot pedal actuator
- In-line strainer
- Drench hose

4211S is a shower and eyewash combination with heavy duty SS 316 piping, SS 316 shower head and eyewash bowls, with a pull rod mechanism for shower and stainless-steel push handle for eyewash.

ANSI Z358.1 2014 complied design delivers consistent water spray for effective decontamination. Pedestal-mounted emergency shower with a stainless-steel showerhead and a stainless-steel stay-open ball valve.

Features

- Pedestal-mounted emergency shower with a stainless-steel showerhead and a stainless-steel stay-open ball valve with a pull rod
- **Showerhead:** Stainless steel showerhead with 20 gallons per minute flow regulator.
- **Valve:** Hands free stainless-steel stay-open ball valve. Unit is provided with a stainless-steel actuator arm and a stainless-steel pull rod.
- **Water Supply:** 1-1/4" NPT female threaded stainless steel side or top inlet.
- **Piping & Mounting:** Schedule 40 stainless steel piping and a stainless-steel floor flange.
- **Universal Sign:** ANSI compliant, vertical identification sign (shower/eyewash sign)
- **Eyewash:** Eyewash with stainless steel 316 bowl, stainless steel nozzles, fitted with 0.4 GPM flow regulators.

Optional Features

- Scald protection valve (SPV)
- Freeze protection valve
- Stainless steel foot pedal actuator
- In-line strainer
- Drench hose





www.smithapplied.com



7040 Virginia Manor Rd.
Beltsville, MD 20705 USA
Phone: +1 (301) 842-4236
Email: info@smithapplied.com